

- 10.4" display with LED backlight
- 1024 × 768 pixels resolution
- Intel Atom E3900 series
- All external interfaces on M12 connectors
- -25 °C to +70 °C (+85 °C), fanless
- Maintenance-free design
- Compliant to IP65 (front) and EN 50155 (railway)
- Linux and Windows support



ROBUST PANEL PC FOR INTERACTIVE RAIL APPLICATIONS

The DC19 panel PC is a rugged, fanless and maintenance-free human-machine interface (HMI) for railway applications. It features a 10.4" display and touch screen. Its small, ultra-flat mechanical design and configuration options save space in the driver cabin and allow the panel to be tailored for all types of applications in different train models. In addition, its full software compatibility with the 12.1" DC20 panel PC both increases flexibility and lowers costs, e.g., if an upgrade to a larger panel is necessary.

HIGH-QUALITY, HIGH-RESOLUTION DISPLAY

The DC19 houses a robust impact-resistant XGA TFT LCD display with LED backlight. It also features LEDs and a light sensor at the front. Due to its high resolution and optimized usability, it is a perfect choice for, e.g., CCTV.

POWERFUL & ENERGY-EFFICIENT COMPUTING

The DC19 is powered by an Intel Atom processor from the E3900 series running at up to 1.6 GHz and equipped with up to 8 GB RAM with ECC and a 32 GB soldered eMMC. Standard interfaces include two Gigabit Ethernet, one CAN, one audio, digital I/O and RS232/RS422/RS485 - all available on M12 connectors at the back of the panel PC.

Two PCI Express Mini Card interfaces can control wireless communication functions like 4G LTE and GNSS. Two micro-SIM card slots with dual-SIM functionality are accessible at the back of the panel.

FLEXIBLE RAIL NETWORK CONNECTION OPTIONS

The DC19 can provide Multifunction Vehicle Bus (MVB) master or slave support where necessary, by adding an MVB PCI Express Mini Card. This makes the display scalable for different applications.

EXTREMELY RUGGED, PERFECTLY RAIL-READY

The DC19 comes with an extremely rugged housing with an IP65 compliant front. It supports a railway-compliant power supply of 24 V DC to 110 V DC, its internal PSU complying with EN 50155 class S2. Also in compliance with the standard, the DC19 operates in a -25 °C to +70 °C environment (+85 °C for 10 minutes), achieved through fanless conduction-cooling technology.

All electronic components are soldered to withstand shock and vibration, backed up by solid M12 connectors, and protected by conformal coating. Long-term availability ensures an extended product life and future-safety. The panel PC meets all important requirements for railway equipment for fast, competitive time-to-market even in mission-critical environments.




www.duagon.com/products/dc19/

DATA SHEET




DC19 | DIAGRAM





DC19 | DIAGRAM



DC19 | TECHNICAL DATA

CPU

- The following CPU types are supported:
 - Intel Atom x5-E3930, 2 cores, 2 threads, 1.3 GHz, 1.8 GHz Turbo Boost, 6.5 W, 2 MB cache
 - Intel Atom x5-E3940, 4 cores, 4 threads, 1.6 GHz, 1.8 GHz Turbo Boost, 9.5 W, 2 MB cache
 - Intel Atom x7-E3950, 4 cores, 4 threads, 1.6 GHz, 2.0 GHz Turbo Boost, 12 W, 2 MB cache

DISPLAY

- Size/Resolution: 10.4" (4:3) / 1024 × 768
- Color depth: 16.2 M
- Luminance: 350 cd/m²
- Viewing angle: 80° / 80° / 80° / 80°



MEMORY

- System RAM
 - Soldered DDR3, ECC
 - 8 GB max.

SECURITY

- Trusted Platform Module 2.0

MASS STORAGE

- eMMC (soldered); 32 GB

WIRELESS FUNCTIONALITY

- Possible functions:
 - GNSS
 - LTE
 - WLAN

INTERFACES

- This product includes interface options
 - Variable I/O in cutouts
- Touch screen
 - Touch technology: PCAP
 - Touch mode: Multi-touch (2 points)
- Light sensor
 - Light sensor position: top left
- Audio
 - 1 × M12, A-coded, receptacle
 - Stereo line input, single-ended
 - Stereo line output, differential
- USB
 - 1 × USB 2.0, M12, A-coded, receptacle, for service
- Ethernet
 - 2 × 10/100/1000BASE-T, M12, X-coded, receptacle
- PCI Express Mini Card
 - 2 × PCI Express Mini Card slot
 - Slot 1: PCIe Full-Mini; PCIe x1, USB 2.0
 - Slot 2: PCIe Full-Mini; PCIe x1, USB 2.0
- SIM card
 - 2 × micro-SIM slot, externally accessible

- Digital I/O
 - 2 × digital input, isolated, M12, B-coded, receptacle
 - 2 × digital output, isolated, M12, B-coded, receptacle
- Serial
 - 1 × RS232/RS422/RS485, isolated, M12, A-coded, receptacle
- CAN bus
 - 1 × CAN isolated, M12, A-coded, receptacle
- LED
 - User configurable: 1 ×
 - Status: power status, system status
- Cutout
 - Antenna connector options: QLS receptacle, RP-SMA receptacle, SMA receptacle
 - D-Sub options: MVB
- Power
 - 1 × power in, M12, A-coded, plug
- Earthing connection
 - M4 stud

SUPERVISION AND CONTROL

- Temperature measurement
- Board management controller
- Real-time clock, buffered by supercapacitor (3 days)

ELECTRICAL SPECIFICATIONS

- Supply voltage: 24 V DC to 110 V DC nom. (EN 50155)
- Power consumption: 30 W max.

MECHANICAL SPECIFICATIONS

- Dimensions: (W) 310 mm, (D) 214 mm, (H) 75 mm ;
Cutout: (W) 281 mm, (H) 206 mm
- Weight: 4.5 kg max.
- Cooling: Air cooling, natural convection, airflow 0.4 m/s
- Protection rating: IP65 (front), IP20 (back and sides)



PRODUCT COMPLIANCE: RAIL - ROLLING STOCK

- Operating temperature: -25 °C to +70 °C, +85 °C for 10 min (EN 50155:2017, class OT3, ST1)
- Rapid temperature variations: EN 50155:2017, class H1, no requirements
- Storage temperature: -40 °C (EN 50155:2017) to +85 °C (EN 60068-2-2, Bb)
- Altitude: +3000 m max. (EN 50125-1:2014, class AX)
- Pollution degree: EN 50124-1:2017, class PD2
- Humidity: +55 °C and +25 °C, 100 % RH max. (EN 50155:2017)
- Shock: 30 ms @ 50 m/s² (EN 61373:2010/AC:2017-09, vehicle body, cat. 1, class B)
- Vibration: 10 min @ 2.02 m/s² (functional) and 5 h @ 11.44 m/s² (long-life) (EN 61373:2010/AC:2017-09, vehicle body, cat. 1, class B, double acceleration)
- Power supply: Interruption of voltage supply: 10 ms (EN 50155:2017, class S2)
- Electrical safety
 - EN 50124-1:2017
 - EN 50153:2014 + A1:2017
 - EN 50155:2017
 - EN ISO 13732-1:2008
- Fire protection: EN 45545-2:2013 + A1:2015, HL3
- EMC emission
 - EN 50121-3-2:2016
 - Regelung Nr. EMV 06 :2014-07-29, Anhang E: Messung an Geräten
 - Regelwerk 50.02.01 :2016-12-01, 12.3.1. EMV - Funk
- EMC immunity: EN 50121-3-2:2016
- Protective coatings
 - EN 50155:2017, class PCX (As agreed between user and supplier)
 - coated: CPU board and IO board coated, both sides not coated: Display Board AF26, display and display electronics / backlight, touch, third party components e.g. LTE, WLAN, ...
- Useful life: 5 years (EN 50155:2017, class L1)
- Display compliance: UIC 612-01

RELIABILITY

- MTBF: 50 000 h predicted @ 40 °C according to IEC/TR 62380 (RDF 2000)

BIOS/BOOT LOADER

- AMI Aptio UEFI Firmware

SOFTWARE SUPPORT


- Linux
 - Supported kernel: 4.8 or higher. For older kernels (e.g., 4.4.x), patches for the Intel Atom E3900 series platform are also available.
 - Driver support
 - Tool support
- Windows
 - Windows 10 IoT Enterprise 64-bit
 - Driver support
 - Tool support
 - Not all functions are supported
- ▶ See the product User Manual for details on software support: www.duagon.com/products/dc19/#doc
- ▶ See also **Application Note Recommendations for a Robust Software Setup**
- ▶ See section Software on the product web page for available packages: www.duagon.com/products/dc19/#downl



DC19 | ORDERING INFORMATION

STANDARD MODELS

09DC19-01 Panel PC, 10.4" touch display, Intel Atom x5-E3930, 1.3 GHz, 4 GB RAM, 24 V DC to 110 V DC, no interface options assembled, conformal coating



duagon | WORLDWIDE

duagon has a global presence with support and sales representatives across 8 countries. With three decentralized engineering and production sites, our customers take advantage of the added competence and flexibility.

www.duagon.com

SWITZERLAND (HQ)

Dietikon
Phone +41 44 743 73 00
sales@duagon.com

AUSTRALIA

Artarmon
Phone +61 2 9966 9424
sales-aus@duagon.com

CHINA

Shanghai
Phone +86 159 0077 2985
sales-chn@duagon.com

FRANCE

Gaillard
Phone +33 450 955 312
sales-fra@duagon.com

GERMANY

Nuremberg
Phone +49 911 99 335 0
sales-deu@duagon.com

INDIA

New Delhi
Phone +91 11 41 61 12 48
sales-ind@duagon.com

SPAIN

Madrid
Phone +34 917 880 610
sales-esp@duagon.com

USA

Blue Bell
Phone +1 215 542 9575
sales-usa@duagon.com