


G403

Binary I/O Card for Railways 3U CompactPCI Serial

- » 4HP PICMG CPCI-S.0 CompactPCI Serial (PCIe 1.0)
- » 16 bidirectional binary I/Os
- » Organized in 4 optically isolated groups
- » Connected via spring cage terminal blocks
- » Flexible I/O configuration
- » Individual edge-triggered interrupts
- » I/O voltage range 14.4 VDC to 154 VDC
- » Current output 1 A at 24 V
- » Driver support for all common operating systems
- » -40 to +85°C with qualified components
- » EN 50155 compliant



Binary I/O for Railway


The G403 is a binary I/O CompactPCI Serial board especially designed for railway applications. The card is used for input/output of digital signals with different voltage levels and ground references. It supports 16 bidirectional digital input/output channels, which are separated into four optically isolated groups.

EN 50155 Compliance

Its voltage range from 14.4 VDC to 154 VDC and its current output of 1 A at 24 V complies with EN 50155, which makes the board ready for immediate use in train applications.

Safety Measures for Mobile Environments

The four front connectors are implemented by using spring cage terminal blocks causing only low wiring outlay and supporting fast installation. The binary railway I/O supports all safety measures necessary for mobile environments like trains including voltage and temperature supervision and readback of outputs.



Binary I/Os

- 16 binary signals
 - 4 optically isolated groups
 - 4 channels for each group
- The following I/O configurations are possible:
 - 16 inputs, or
 - 16 outputs, or
 - any combination of inputs and outputs
- Individual edge-triggered interrupts
- High-side output switches
- High output current: max. 1 A per channel at 24 V
- Temperature and voltage supervision

Output Characteristics

- Output voltage range
 - Limits continuous: 0 VDC to +138 VDC
 - Limits (duration <1s): 0 VDC to +154 VDC
- Switching time for output change: 400 µs (rise time) / 600 µs (fall time)

Input Characteristics

- Input voltage range
 - Limits continuous: -0.7 VDC to +138 VDC
 - Limits (duration <1s): -0.7 VDC to +154 VDC
- Input voltage of external supply voltage
 - Can be configured individually for each group
 - Nominal: +24 VDC to +110 VDC
 - Limits continuous: +16.8 VDC to +138 VDC
 - Limits (duration <1s): +14.4 VDC to +154 VDC
- Switching threshold: 40% (+15%/-15%) of external supply voltage

Front Interfaces

- 4 spring cage terminal blocks

Backplane Standard

- Compliance with CompactPCI Serial PICMG CPCI-S.0 Specification
- Peripheral slot
- P1 connector with geographical addressing for distinguishing boards in a system with several boards

Electrical Specifications

- Supply voltage
 - +12V (9.5 to 15.5 V)
- Power consumption
 - 5 W max.
- Isolation voltage:
 - 1500 VAC between isolated side and digital side
 - 1500 VAC between the channels

Mechanical Specifications

- Dimensions
 - 3U, 4 HP
- Weight: approx. 285 g

Environmental Specifications

- Temperature range (operation):
 - -40..+85°C (qualified components)
 - Airflow: 1.0 m/s
- Temperature range (storage): -40..+85°C
- Cooling concept
 - Convection cooling
- Relative humidity (operation): max. 95% non-condensing
- Relative humidity (storage): max. 95% non-condensing
- Altitude: -300 m to +3000 m
- Shock: EN 50155 (12.2.11) / EN 61373 category 1 class B body mounted
- Vibration: EN 50155 (12.2.11) / EN 61373 category 1 class B body mounted
- Conformal coating (standard)

Reliability

- MTBF: tbd h @ 40°C according to IEC/TR 62380 (RDF 2000)

Safety

- Flammability
 - UL 94V-0
- Electrical Safety
 - EN 62368-1 (former EN 60950-1)
 - Insulation measurement: EN 50155 (12.2.9.1)
 - Voltage withstand: EN 50155 (12.2.9.2)

EMC Conformity

- EN 55011 (radio disturbance)
- IEC 61000-4-2 (ESD)
- IEC 61000-4-3 (electromagnetic field immunity)
- IEC 61000-4-4 (burst)
- IEC 61000-4-5 (surge)
- IEC 61000-4-6 (conducted disturbances)

Software Support

- The G403 is supported by standard OS UART drivers
- [A demo application for Linux, Windows and VxWorks is available under Downloads.](#)

Germany

MEN Mikro Elektronik GmbH

Neuwieder Straße 3-7
90411 Nuremberg
Phone +49-911-99 33 5-0

sales@men.de
www.men.de

USA

MEN Micro Inc.

860 Penllyn Blue Bell Pike
Blue Bell, PA 19422
Phone 215-542-9575

sales@menmicro.com
www.menmicro.com

France

MEN Mikro Elektronik SAS

18, rue René Cassin
ZA de la Châtelaine
74240 Gaillard
Phone +33-450-955-312

sales@men-france.fr
www.men-france.fr

China

MEN Mikro Elektronik (Shanghai) Co., Ltd.

Room 808-809, Jiaxing Mansion, No. 877 Dongfang Road
200122 Shanghai
Phone +86-21-5058-0961

sales@men-china.cn
www.men-china.cn

Up-to-date information, documentation and ordering information:
www.men.de/products/g403/

The date of issue stated in this data sheet refers to the Technical Data only. Changes in ordering information given herein do not affect the date of issue. All brand or product names are trademarks or registered trademarks of their respective holders.

MEN is not responsible for the results of any actions taken on the basis of information in the publication, nor for any error in or omission from the publication.

MEN expressly disclaims all and any liability and responsibility to any person, whether a reader of the publication or not, in respect of anything, and of the consequences of anything, done or omitted to be done by any such person in reliance, whether wholly or partially, on the whole or any part of the contents of the publication.

The correct function of MEN products in mission-critical and life-critical applications is limited to the environmental specification given for each product in the technical user manual. The correct function of MEN products under extended environmental conditions is limited to the individual requirement specification and subsequent validation documents for each product for the applicable use case and has to be agreed upon in writing by MEN and the customer. Should the customer purchase or use MEN products for any unintended or unauthorized application, the customer shall indemnify and hold MEN and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim or personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that MEN was negligent regarding the design or manufacture of the part.

In no case is MEN liable for the correct function of the technical installation where MEN products are a part of.

© 2016 MEN